



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height		
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters
15 Ft. (4.6 m)	7	E-01507	2,978	79	71	84	76	18'-10"	5.73	22'-8"	6.92
	8	E-01508	3,373	89	81	95	86	21'-6"	6.55	25'-5"	7.74
	9	E-01509	3,769	100	90	106	96	24'-2"	7.38	28'-0"	8.53
	10	E-01510	4,165	110	100	117	106	26'-10"	8.17	30'-8"	9.36
	11	E-01511	4,561	120	109	129	117	29'-6"	8.99	33'-5"	10.18
	12	E-01512	4,957	131	119	140	127	32'-2"	9.81	36'-0"	10.97
	13	E-01513	5,353	141	128	151	137	34'-10"	10.61	38'-8"	11.80
	14	E-01514	5,749	152	138	162	147	37'-6"	11.43	41'-5"	12.62
	15	E-01515	6,145	162	147	173	157	40'-2"	12.25	44'-0"	13.41
	16	E-01516	6,540	173	157	184	167	42'-10"	13.05	46'-8"	14.23
	17	E-01517	6,936	183	166	195	177	45'-6"	13.87	49'-5"	15.06
	18	E-01518	7,332	194	176	207	187	48'-2"	14.69	52'-0"	15.85
	19	E-01519	7,728	204	185	218	198	50'-10"	15.48	54'-8"	16.67
	20	E-01520	8,124	215	195	229	208	53'-6"	16.31	57'-5"	17.50
18 Ft. (5.5 m)	21	E-01521	8,520	225	204	240	218	56'-2"	17.13	60'-0"	18.29
	22	E-01522	8,916	236	214	251	228	58'-10"	17.92	62'-8"	19.11
	7	E-01807	4,347	115	104	122	111	18'-10"	5.73	23'-6"	7.16
	8	E-01808	4,917	130	118	139	126	21'-6"	6.55	26'-2"	7.99
	9	E-01809	5,487	145	131	155	140	24'-2"	7.38	28'-11"	8.81
	10	E-01810	6,058	160	145	171	155	26'-10"	8.17	31'-6"	9.60
	11	E-01811	6,628	175	159	187	169	29'-6"	8.99	34'-2"	10.42
	12	E-01812	7,198	190	173	203	184	32'-2"	9.81	36'-11"	11.25
	13	E-01813	7,769	205	186	219	199	34'-10"	10.61	39'-6"	12.04
	14	E-01814	8,339	220	200	235	213	37'-6"	11.43	42'-2"	12.86
	15	E-01815	8,909	235	214	251	228	40'-2"	12.25	44'-11"	13.69
	16	E-01816	9,480	250	227	267	242	42'-10"	13.05	47'-6"	14.48
	17	E-01817	10,050	265	241	283	257	45'-6"	13.87	50'-2"	15.30
	18	E-01818	10,621	281	255	299	271	48'-2"	14.69	52'-11"	16.12
19	E-01819	11,191	296	268	315	286	50'-10"	15.48	55'-6"	16.92	
20	E-01820	11,761	311	282	331	301	53'-6"	16.31	58'-2"	17.74	
21	E-01821	12,332	326	296	347	315	56'-2"	17.13	60'-11"	18.56	
22	E-01822	12,902	341	309	364	330	58'-10"	17.92	63'-6"	19.35	
23	E-01823	13,472	356	323	380	344	61'-6"	18.75	66'-2"	20.18	
24	E-01824	14,043	371	337	396	359	64'-2"	19.57	68'-11"	21.00	
25	E-01825	14,613	386	350	412	374	66'-10"	20.36	71'-6"	21.79	
26	E-01826	15,184	401	364	428	388	69'-6"	21.18	74'-2"	22.62	



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height			
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters	
21 Ft. (6.4 m)	7	E-02107	5,995	158	144	169	153	18'-10"	5.73	24'-5"	7.44	
	8	E-02108	6,772	179	162	191	173	21'-6"	6.55	27'-1"	8.26	
	9	E-02109	7,549	199	181	213	193	24'-2"	7.38	29'-8"	9.05	
	10	E-02110	8,325	220	200	235	213	26'-10"	8.17	32'-5"	9.88	
	11	E-02111	9,102	240	218	256	233	29'-6"	8.99	35'-1"	10.70	
	12	E-02112	9,879	261	237	278	253	32'-2"	9.81	37'-8"	11.49	
	13	E-02113	10,655	281	255	300	272	34'-10"	10.61	40'-5"	12.31	
	14	E-02114	11,432	302	274	322	292	37'-6"	11.43	43'-1"	13.14	
	15	E-02115	12,209	322	293	344	312	40'-2"	12.25	45'-8"	13.93	
	16	E-02116	12,985	343	311	366	332	42'-10"	13.05	48'-5"	14.75	
	17	E-02117	13,762	364	330	388	352	45'-6"	13.87	51'-1"	15.58	
	18	E-02118	14,538	384	348	410	372	48'-2"	14.69	53'-8"	16.37	
	19	E-02119	15,315	405	367	432	391	50'-10"	15.48	56'-5"	17.19	
	20	E-02120	16,092	425	386	453	411	53'-6"	16.31	59'-1"	18.01	
	21	E-02121	16,868	446	404	475	431	56'-2"	17.13	61'-8"	18.81	
	22	E-02122	17,645	466	423	497	451	58'-10"	17.92	64'-5"	19.63	
	23	E-02123	18,422	487	441	519	471	61'-6"	18.75	67'-1"	20.45	
	24	E-02124	19,198	507	460	541	491	64'-2"	19.57	69'-8"	21.24	
	25	E-02125	19,975	528	479	563	511	66'-10"	20.36	72'-5"	22.07	
	26	E-02126	20,751	548	497	585	530	69'-6"	21.18	75'-1"	22.89	
	27	E-02127	21,528	569	516	607	550	72'-2"	22.01	77'-8"	23.68	
	28	E-02128	22,305	589	535	628	570	74'-10"	22.80	80'-5"	24.51	
	29	E-02129	23,081	610	553	650	590	77'-6"	23.62	83'-1"	25.33	
	30	E-02130	23,858	630	572	672	610	80'-2"	24.44	85'-8"	26.12	
	24 Ft. (7.3 m)	7	E-02407	7,934	210	190	224	203	18'-10"	5.73	25'-4"	7.71
		8	E-02408	8,948	236	214	252	229	21'-6"	6.55	27'-11"	8.50
		9	E-02409	9,963	263	239	281	255	24'-2"	7.38	30'-7"	9.33
		10	E-02410	10,978	290	263	309	281	26'-10"	8.17	33'-4"	10.15
		11	E-02411	11,992	317	287	338	307	29'-6"	8.99	35'-11"	10.94
		12	E-02412	13,007	344	312	366	332	32'-2"	9.81	38'-7"	11.77
13		E-02413	14,022	370	336	395	358	34'-10"	10.61	41'-4"	12.59	
14		E-02414	15,036	397	360	424	384	37'-6"	11.43	43'-11"	13.38	
15		E-02415	16,051	424	385	452	410	40'-2"	12.25	46'-7"	14.20	
16		E-02416	17,066	451	409	481	436	42'-10"	13.05	49'-4"	15.03	
17		E-02417	18,080	478	433	509	462	45'-6"	13.87	51'-11"	15.82	
18		E-02418	19,095	504	458	538	488	48'-2"	14.69	54'-7"	16.64	
19		E-02419	20,110	531	482	567	514	50'-10"	15.48	57'-4"	17.47	
20		E-02420	21,124	558	506	595	540	53'-6"	16.31	59'-11"	18.26	
21		E-02421	22,139	585	531	624	566	56'-2"	17.13	62'-7"	19.08	
22		E-02422	23,154	612	555	652	592	58'-10"	17.92	65'-4"	19.90	
23		E-02423	24,168	638	579	681	618	61'-6"	18.75	67'-11"	20.70	
24		E-02424	25,183	665	603	710	644	64'-2"	19.57	70'-7"	21.52	
25		E-02425	26,198	692	628	738	670	66'-10"	20.36	73'-4"	22.34	
26		E-02426	27,212	719	652	767	696	69'-6"	21.18	75'-11"	23.13	
27		E-02427	28,227	746	676	795	722	72'-2"	22.01	78'-7"	23.96	
28		E-02428	29,242	772	701	824	747	74'-10"	22.80	81'-4"	24.78	
29		E-02429	30,257	799	725	853	773	77'-6"	23.62	83'-11"	25.57	
30		E-02430	31,271	826	749	881	799	80'-2"	24.44	86'-7"	26.40	
31		E-02431	32,286	853	774	910	825	82'-10"	25.24	89'-4"	27.22	
32		E-02432	33,301	880	798	938	851	85'-6"	26.06	91'-11"	28.01	
33		E-02433	34,315	906	822	967	877	88'-2"	26.88	94'-7"	28.83	
34		E-02434	35,330	933	847	995	903	90'-10"	27.68	97'-4"	29.66	
35		E-02435	36,345	960	871	1,024	929	93'-6"	28.50	99'-11"	30.45	



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height		
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters
27 Ft. (8.2 m)	7	E-02707	10,171	269	244	287	260	18'-10"	5.73	26'-1"	7.96
	8	E-02708	11,455	303	275	323	293	21'-6"	6.55	28'-10"	8.78
	9	E-02709	12,740	337	305	359	326	24'-2"	7.38	31'-6"	9.60
	10	E-02710	14,024	370	336	395	358	26'-10"	8.17	34'-1"	10.39
	11	E-02711	15,309	404	367	431	391	29'-6"	8.99	36'-10"	11.22
	12	E-02712	16,593	438	398	468	424	32'-2"	9.81	39'-6"	12.04
	13	E-02713	17,878	472	428	504	457	34'-10"	10.61	42'-1"	12.83
	14	E-02714	19,162	506	459	540	490	37'-6"	11.43	44'-10"	13.66
	15	E-02715	20,447	540	490	576	523	40'-2"	12.25	47'-6"	14.48
	16	E-02716	21,731	574	521	612	555	42'-10"	13.05	50'-1"	15.27
	17	E-02717	23,016	608	552	648	588	45'-6"	13.87	52'-10"	16.09
	18	E-02718	24,300	642	582	685	621	48'-2"	14.69	55'-6"	16.92
	19	E-02719	25,585	676	613	721	654	50'-10"	15.48	58'-1"	17.71
	20	E-02720	26,869	710	644	757	687	53'-6"	16.31	60'-10"	18.53
	21	E-02721	28,154	744	675	793	720	56'-2"	17.13	63'-6"	19.35
	22	E-02722	29,438	778	705	829	752	58'-10"	17.92	66'-1"	20.15
	23	E-02723	30,722	812	736	866	785	61'-6"	18.75	68'-10"	20.97
	24	E-02724	32,007	845	767	902	818	64'-2"	19.57	71'-6"	21.79
	25	E-02725	33,291	879	798	938	851	66'-10"	20.36	74'-1"	22.59
	26	E-02726	34,576	913	829	974	884	69'-6"	21.18	76'-10"	23.41
	27	E-02727	35,860	947	859	1,010	917	72'-2"	22.01	79'-6"	24.23
	28	E-02728	37,145	981	890	1,047	949	74'-10"	22.80	82'-1"	25.02
	29	E-02729	38,429	1,015	921	1,083	982	77'-6"	23.62	84'-10"	25.85
	30	E-02730	39,714	1,049	952	1,119	1,015	80'-2"	24.44	87'-6"	26.67
	31	E-02731	40,998	1,083	982	1,155	1,048	82'-10"	25.24	90'-1"	27.46
	32	E-02732	42,283	1,117	1,013	1,191	1,081	85'-6"	26.06	92'-10"	28.29
	33	E-02733	43,567	1,151	1,044	1,228	1,114	88'-2"	26.88	95'-6"	29.11
	34	E-02734	44,852	1,185	1,075	1,264	1,146	90'-10"	27.68	98'-1"	29.90
	35	E-02735	46,136	1,219	1,106	1,300	1,179	93'-6"	28.50	100'-10"	30.72
	36	E-02736	47,421	1,253	1,136	1,336	1,212	96'-2"	29.32	103'-6"	31.55
	37	E-02737	48,705	1,287	1,167	1,372	1,245	98'-10"	30.11	106'-1"	32.34
	38	E-02738	49,990	1,320	1,198	1,409	1,278	101'-6"	30.94	108'-10"	33.16
	39	E-02739	51,274	1,354	1,229	1,445	1,311	104'-2"	31.76	111'-6"	33.99



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height		
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters
30 Ft. (9.1 m)	7	E-03007	12,716	336	305	358	325	18'-10"	5.73	27'-0"	8.23
	8	E-03008	14,302	378	343	403	366	21'-6"	6.55	29'-8"	9.05
	9	E-03009	15,888	420	381	448	406	24'-2"	7.38	32'-4"	9.85
	10	E-03010	17,474	462	419	492	447	26'-10"	8.17	35'-0"	10.67
	11	E-03011	19,060	503	457	537	487	29'-6"	8.99	37'-8"	11.49
	12	E-03012	20,646	545	495	582	528	32'-2"	9.81	40'-4"	12.28
	13	E-03013	22,232	587	533	626	568	34'-10"	10.61	43'-0"	13.11
	14	E-03014	23,818	629	571	671	609	37'-6"	11.43	45'-8"	13.93
	15	E-03015	25,405	671	609	716	649	40'-2"	12.25	48'-4"	14.72
	16	E-03016	26,991	713	647	760	690	42'-10"	13.05	51'-0"	15.54
	17	E-03017	28,577	755	685	805	730	45'-6"	13.87	53'-8"	16.37
	18	E-03018	30,163	797	723	850	771	48'-2"	14.69	56'-4"	17.16
	19	E-03019	31,749	839	761	895	812	50'-10"	15.48	59'-0"	17.98
	20	E-03020	33,335	881	799	939	852	53'-6"	16.31	61'-8"	18.81
	21	E-03021	34,921	922	837	984	893	56'-2"	17.13	64'-4"	19.60
	22	E-03022	36,507	964	875	1,029	933	58'-10"	17.92	67'-0"	20.42
	23	E-03023	38,093	1,006	913	1,073	974	61'-6"	18.75	69'-8"	21.24
	24	E-03024	39,679	1,048	951	1,118	1,014	64'-2"	19.57	72'-4"	22.04
	25	E-03025	41,265	1,090	989	1,163	1,055	66'-10"	20.36	75'-0"	22.86
	26	E-03026	42,851	1,132	1,027	1,207	1,095	69'-6"	21.18	77'-8"	23.68
	27	E-03027	44,437	1,174	1,065	1,252	1,136	72'-2"	22.01	80'-4"	24.48
	28	E-03028	46,023	1,216	1,103	1,297	1,176	74'-10"	22.80	83'-0"	25.30
	29	E-03029	47,610	1,258	1,141	1,341	1,217	77'-6"	23.62	85'-8"	26.12
	30	E-03030	49,196	1,300	1,179	1,386	1,258	80'-2"	24.44	88'-4"	26.91
	31	E-03031	50,782	1,341	1,217	1,431	1,298	82'-10"	25.24	91'-0"	27.74
	32	E-03032	52,368	1,383	1,255	1,476	1,339	85'-6"	26.06	93'-8"	28.56
	33	E-03033	53,954	1,425	1,293	1,520	1,379	88'-2"	26.88	96'-4"	29.35
	34	E-03034	55,540	1,467	1,331	1,565	1,420	90'-10"	27.68	99'-0"	30.18
	35	E-03035	57,126	1,509	1,369	1,610	1,460	93'-6"	28.50	101'-8"	31.00
	36	E-03036	58,712	1,551	1,407	1,654	1,501	96'-2"	29.32	104'-4"	31.79
	37	E-03037	60,298	1,593	1,445	1,699	1,541	98'-10"	30.11	107'-0"	32.61
	38	E-03038	61,884	1,635	1,483	1,744	1,582	101'-6"	30.94	109'-8"	33.44
	39	E-03039	63,470	1,677	1,521	1,788	1,622	104'-2"	31.76	112'-4"	34.23
	40	E-03040	65,056	1,718	1,559	1,833	1,663	106'-10"	32.55	115'-0"	35.05



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height		
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters
33 Ft. (10.1 m)	7	E-03307	15,579	412	373	439	398	18'-10"	5.73	27'-11"	8.50
	8	E-03308	17,498	462	419	493	447	21'-6"	6.55	30'-6"	9.30
	9	E-03309	19,418	513	465	547	496	24'-2"	7.38	33'-2"	10.12
	10	E-03310	21,337	564	511	601	545	26'-10"	8.17	35'-11"	10.94
	11	E-03311	23,257	614	557	655	594	29'-6"	8.99	38'-6"	11.73
	12	E-03312	25,176	665	603	709	644	32'-2"	9.81	41'-2"	12.56
	13	E-03313	27,096	716	649	763	693	34'-10"	10.61	43'-11"	13.38
	14	E-03314	29,015	766	695	818	742	37'-6"	11.43	46'-6"	14.17
	15	E-03315	30,934	817	741	872	791	40'-2"	12.25	49'-2"	15.00
	16	E-03316	32,854	868	787	926	840	42'-10"	13.05	51'-11"	15.82
	17	E-03317	34,773	919	833	980	889	45'-6"	13.87	54'-6"	16.61
	18	E-03318	36,693	969	879	1,034	938	48'-2"	14.69	57'-2"	17.43
	19	E-03319	38,612	1,020	925	1,088	987	50'-10"	15.48	59'-11"	18.26
	20	E-03320	40,532	1,071	971	1,142	1,036	53'-6"	16.31	62'-6"	19.05
	21	E-03321	42,451	1,121	1,017	1,196	1,085	56'-2"	17.13	65'-2"	19.87
	22	E-03322	44,370	1,172	1,063	1,250	1,134	58'-10"	17.92	67'-11"	20.70
	23	E-03323	46,290	1,223	1,109	1,304	1,183	61'-6"	18.75	70'-6"	21.49
	24	E-03324	48,209	1,273	1,155	1,358	1,232	64'-2"	19.57	73'-2"	22.31
	25	E-03325	50,129	1,324	1,201	1,412	1,281	66'-10"	20.36	75'-11"	23.13
	26	E-03326	52,048	1,375	1,247	1,467	1,330	69'-6"	21.18	78'-6"	23.93
	27	E-03327	53,968	1,426	1,293	1,521	1,379	72'-2"	22.01	81'-2"	24.75
	28	E-03328	55,887	1,476	1,339	1,575	1,429	74'-10"	22.80	83'-11"	25.57
	29	E-03329	57,806	1,527	1,385	1,629	1,478	77'-6"	23.62	86'-6"	26.37
	30	E-03330	59,726	1,578	1,431	1,683	1,527	80'-2"	24.44	89'-2"	27.19
	31	E-03331	61,645	1,628	1,477	1,737	1,576	82'-10"	25.24	91'-11"	28.01
	32	E-03332	63,565	1,679	1,523	1,791	1,625	85'-6"	26.06	94'-6"	28.80
	33	E-03333	65,484	1,730	1,569	1,845	1,674	88'-2"	26.88	97'-2"	29.63
	34	E-03334	67,404	1,780	1,615	1,899	1,723	90'-10"	27.68	99'-11"	30.45
	35	E-03335	69,323	1,831	1,661	1,953	1,772	93'-6"	28.50	102'-6"	31.24
	36	E-03336	71,242	1,882	1,707	2,007	1,821	96'-2"	29.32	105'-2"	32.06
	37	E-03337	73,162	1,933	1,753	2,061	1,870	98'-10"	30.11	107'-11"	32.89
	38	E-03338	75,081	1,983	1,799	2,116	1,919	101'-6"	30.94	110'-6"	33.68
	39	E-03339	77,001	2,034	1,845	2,170	1,968	104'-2"	31.76	113'-2"	34.50
	40	E-03340	78,920	2,085	1,891	2,224	2,017	106'-10"	32.55	115'-11"	35.33



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height		
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters
36 Ft. (11.0 m)	7	E-03607	18,769	496	450	529	480	18'-10"	5.73	28'-8"	8.75
	8	E-03608	21,054	556	505	593	538	21'-6"	6.55	31'-5"	9.57
	9	E-03609	23,338	616	559	658	597	24'-2"	7.38	34'-0"	10.36
	10	E-03610	25,623	677	614	722	655	26'-10"	8.17	36'-8"	11.19
	11	E-03611	27,907	737	669	786	713	29'-6"	8.99	39'-5"	12.01
	12	E-03612	30,192	798	724	851	772	32'-2"	9.81	42'-0"	12.80
	13	E-03613	32,476	858	778	915	830	34'-10"	10.61	44'-8"	13.62
	14	E-03614	34,761	918	833	979	889	37'-6"	11.43	47'-5"	14.45
	15	E-03615	37,046	979	888	1,044	947	40'-2"	12.25	50'-0"	15.24
	16	E-03616	39,330	1,039	943	1,108	1,005	42'-10"	13.05	52'-8"	16.06
	17	E-03617	41,615	1,099	997	1,173	1,064	45'-6"	13.87	55'-5"	16.89
	18	E-03618	43,899	1,160	1,052	1,237	1,122	48'-2"	14.69	58'-0"	17.68
	19	E-03619	46,184	1,220	1,107	1,301	1,181	50'-10"	15.48	60'-8"	18.50
	20	E-03620	48,468	1,280	1,161	1,366	1,239	53'-6"	16.31	63'-5"	19.32
	21	E-03621	50,753	1,341	1,216	1,430	1,297	56'-2"	17.13	66'-0"	20.12
	22	E-03622	53,037	1,401	1,271	1,494	1,356	58'-10"	17.92	68'-8"	20.94
	23	E-03623	55,322	1,461	1,326	1,559	1,414	61'-6"	18.75	71'-5"	21.76
	24	E-03624	57,607	1,522	1,380	1,623	1,473	64'-2"	19.57	74'-0"	22.56
	25	E-03625	59,891	1,582	1,435	1,688	1,531	66'-10"	20.36	76'-8"	23.38
	26	E-03626	62,176	1,642	1,490	1,752	1,589	69'-6"	21.18	79'-5"	24.20
	27	E-03627	64,460	1,703	1,545	1,816	1,648	72'-2"	22.01	82'-0"	24.99
	28	E-03628	66,745	1,763	1,599	1,881	1,706	74'-10"	22.80	84'-8"	25.82
	29	E-03629	69,029	1,823	1,654	1,945	1,764	77'-6"	23.62	87'-5"	26.64
	30	E-03630	71,314	1,884	1,709	2,009	1,823	80'-2"	24.44	90'-0"	27.43
	31	E-03631	73,599	1,944	1,764	2,074	1,881	82'-10"	25.24	92'-8"	28.25
	32	E-03632	75,883	2,004	1,818	2,138	1,940	85'-6"	26.06	95'-5"	29.08
	33	E-03633	78,168	2,065	1,873	2,202	1,998	88'-2"	26.88	98'-0"	29.87
	34	E-03634	80,452	2,125	1,928	2,267	2,056	90'-10"	27.68	100'-8"	30.69
	35	E-03635	82,737	2,186	1,983	2,331	2,115	93'-6"	28.50	103'-5"	31.52
	36	E-03636	85,021	2,246	2,037	2,396	2,173	96'-2"	29.32	106'-0"	32.31
	37	E-03637	87,306	2,306	2,092	2,460	2,232	98'-10"	30.11	108'-8"	33.13
	38	E-03638	89,590	2,367	2,147	2,524	2,290	101'-6"	30.94	111'-5"	33.95
	39	E-03639	91,875	2,427	2,202	2,589	2,348	104'-2"	31.76	114'-0"	34.75
	40	E-03640	94,160	2,487	2,256	2,653	2,407	106'-10"	32.55	116'-8"	35.57



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height		
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters
42 Ft. (12.8 m)	8	E-04208	29,279	773	702	825	748	21'-6"	6.55	33'-2"	10.12
	9	E-04209	32,389	856	776	913	828	24'-2"	7.38	35'-10"	10.91
	10	E-04210	35,499	938	851	1,000	907	26'-10"	8.17	38'-6"	11.73
	11	E-04211	38,609	1,020	925	1,088	987	29'-6"	8.99	41'-2"	12.56
	12	E-04212	41,719	1,102	1,000	1,175	1,066	32'-2"	9.81	43'-10"	13.35
	13	E-04213	44,829	1,184	1,074	1,263	1,146	34'-10"	10.61	46'-6"	14.17
	14	E-04214	47,940	1,266	1,149	1,351	1,225	37'-6"	11.43	49'-2"	15.00
	15	E-04215	51,050	1,348	1,223	1,438	1,305	40'-2"	12.25	51'-10"	15.79
	16	E-04216	54,160	1,431	1,298	1,526	1,384	42'-10"	13.05	54'-6"	16.61
	17	E-04217	57,270	1,513	1,372	1,614	1,464	45'-6"	13.87	57'-2"	17.43
	18	E-04218	60,380	1,595	1,447	1,701	1,543	48'-2"	14.69	59'-10"	18.23
	19	E-04219	63,490	1,677	1,521	1,789	1,623	50'-10"	15.48	62'-6"	19.05
	20	E-04220	66,600	1,759	1,596	1,877	1,702	53'-6"	16.31	65'-2"	19.87
	21	E-04221	69,711	1,841	1,671	1,964	1,782	56'-2"	17.13	67'-10"	20.67
	22	E-04222	72,821	1,924	1,745	2,052	1,861	58'-10"	17.92	70'-6"	21.49
	23	E-04223	75,931	2,006	1,820	2,139	1,941	61'-6"	18.75	73'-2"	22.31
	24	E-04224	79,041	2,088	1,894	2,227	2,020	64'-2"	19.57	75'-10"	23.10
	25	E-04225	82,151	2,170	1,969	2,315	2,100	66'-10"	20.36	78'-6"	23.93
	26	E-04226	85,261	2,252	2,043	2,402	2,179	69'-6"	21.18	81'-2"	24.75
	27	E-04227	88,371	2,334	2,118	2,490	2,259	72'-2"	22.01	83'-10"	25.54
	28	E-04228	91,482	2,417	2,192	2,578	2,338	74'-10"	22.80	86'-6"	26.37
	29	E-04229	94,592	2,499	2,267	2,665	2,418	77'-6"	23.62	89'-2"	27.19
	30	E-04230	97,702	2,581	2,341	2,753	2,497	80'-2"	24.44	91'-10"	27.98
	31	E-04231	100,812	2,663	2,416	2,841	2,577	82'-10"	25.24	94'-6"	28.80
	32	E-04232	103,922	2,745	2,490	2,928	2,656	85'-6"	26.06	97'-2"	29.63
	33	E-04233	107,032	2,827	2,565	3,016	2,736	88'-2"	26.88	99'-10"	30.42
	34	E-04234	110,142	2,909	2,639	3,103	2,815	90'-10"	27.68	102'-6"	31.24
	35	E-04235	113,253	2,992	2,714	3,191	2,895	93'-6"	28.50	105'-2"	32.06
	36	E-04236	116,363	3,074	2,788	3,279	2,974	96'-2"	29.32	107'-10"	32.86
	37	E-04237	119,473	3,156	2,863	3,366	3,054	98'-10"	30.11	110'-6"	33.68
	38	E-04238	122,583	3,238	2,938	3,454	3,133	101'-6"	30.94	113'-2"	34.50
	39	E-04239	125,693	3,320	3,012	3,542	3,213	104'-2"	31.76	115'-10"	35.30
	40	E-04240	128,803	3,402	3,087	3,629	3,292	106'-10"	32.55	118'-6"	36.12



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height		
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters
48 Ft. (14.6 m)	8	E-04808 ^{1 2}	39,053	1,032	936	1,100	998	21'-6"	6.55	33'-10"	10.30
	9	E-04809 ^{1 2}	43,116	1,139	1,033	1,215	1,102	24'-2"	7.38	36'-6"	11.13
	10	E-04810 ^{1 2}	47,179	1,246	1,131	1,329	1,206	26'-10"	8.17	39'-1"	11.92
	11	E-04811 ^{1 2}	51,241	1,354	1,228	1,444	1,310	29'-6"	8.99	41'-10"	12.74
	12	E-04812 ^{1 2}	55,304	1,461	1,325	1,558	1,414	32'-2"	9.81	44'-6"	13.56
	13	E-04813 ^{1 2}	59,367	1,568	1,423	1,673	1,518	34'-10"	10.61	47'-1"	14.36
	14	E-04814 ^{1 2}	63,430	1,676	1,520	1,787	1,621	37'-6"	11.43	49'-10"	15.18
	15	E-04815 ^{1 2}	67,493	1,783	1,617	1,902	1,725	40'-2"	12.25	52'-6"	16.00
	16	E-04816 ¹	71,555	1,890	1,715	2,016	1,829	42'-10"	13.05	55'-1"	16.79
	17	E-04817 ¹	75,618	1,997	1,812	2,131	1,933	45'-6"	13.87	57'-10"	17.62
	18	E-04818 ¹	79,681	2,105	1,909	2,245	2,037	48'-2"	14.69	60'-6"	18.44
	19	E-04819 ¹	83,744	2,212	2,007	2,360	2,141	50'-10"	15.48	63'-1"	19.23
	20	E-04820 ¹	87,807	2,319	2,104	2,474	2,244	53'-6"	16.31	65'-10"	20.06
	21	E-04821 ¹	91,870	2,427	2,202	2,589	2,348	56'-2"	17.13	68'-6"	20.88
	22	E-04822 ¹	95,932	2,534	2,299	2,703	2,452	58'-10"	17.92	71'-1"	21.67
	23	E-04823 ¹	99,995	2,641	2,396	2,818	2,556	61'-6"	18.75	73'-10"	22.49
	24	E-04824 ¹	104,058	2,749	2,494	2,932	2,660	64'-2"	19.57	76'-6"	23.32
	25	E-04825 ¹	108,121	2,856	2,591	3,046	2,764	66'-10"	20.36	79'-1"	24.11
	26	E-04826 ¹	112,184	2,963	2,688	3,161	2,868	69'-6"	21.18	81'-10"	24.93
	27	E-04827 ¹	116,246	3,071	2,786	3,275	2,971	72'-2"	22.01	84'-6"	25.76
	28	E-04828 ¹	120,309	3,178	2,883	3,390	3,075	74'-10"	22.80	87'-1"	26.55
	29	E-04829 ¹	124,372	3,285	2,980	3,504	3,179	77'-6"	23.62	89'-10"	27.37
	30	E-04830 ¹	128,435	3,393	3,078	3,619	3,283	80'-2"	24.44	92'-6"	28.19
	31	E-04831 ¹	132,498	3,500	3,175	3,733	3,387	82'-10"	25.24	95'-1"	28.99
	32	E-04832 ¹	136,561	3,607	3,273	3,848	3,491	85'-6"	26.06	97'-10"	29.81
	33	E-04833 ¹	140,623	3,715	3,370	3,962	3,595	88'-2"	26.88	100'-6"	30.63
	34	E-04834 ¹	144,686	3,822	3,467	4,077	3,698	90'-10"	27.68	103'-1"	31.42
	35	E-04835 ¹	148,749	3,929	3,565	4,191	3,802	93'-6"	28.50	105'-10"	32.25
	36	E-04836 ¹	152,812	4,037	3,662	4,306	3,906	96'-2"	29.32	108'-6"	33.07
	37	E-04837 ¹	156,875	4,144	3,759	4,420	4,010	98'-10"	30.11	111'-1"	33.86
	38	E-04838 ¹	160,937	4,251	3,857	4,535	4,114	101'-6"	30.94	113'-10"	34.69
	39	E-04839 ¹	165,000	4,359	3,954	4,649	4,218	104'-2"	31.76	116'-6"	35.51
	40	E-04840 ¹	169,063	4,466	4,051	4,764	4,321	106'-10"	32.55	119'-1"	36.30



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height		
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters
54 Ft. (16.5 m)	8	E-05408 †	50,450	1,333	1,209	1,422	1,290	21'-6"	6.55	35'-6"	10.82
	9	E-05409 †	55,593	1,468	1,332	1,566	1,421	24'-2"	7.38	38'-2"	11.64
	10	E-05410 †	60,735	1,604	1,455	1,711	1,552	26'-10"	8.17	40'-10"	12.44
	11	E-05411 †	65,877	1,740	1,579	1,856	1,684	29'-6"	8.99	43'-6"	13.26
	12	E-05412 †	71,020	1,876	1,702	2,001	1,815	32'-2"	9.81	46'-2"	14.08
	13	E-05413 †	76,162	2,012	1,825	2,146	1,947	34'-10"	10.61	48'-10"	14.87
	14	E-05414 †	81,305	2,148	1,948	2,291	2,078	37'-6"	11.43	51'-6"	15.70
	15	E-05415 †	86,447	2,284	2,072	2,436	2,210	40'-2"	12.25	54'-2"	16.52
	16	E-05416 †	91,589	2,419	2,195	2,581	2,341	42'-10"	13.05	56'-10"	17.31
	17	E-05417 †	96,732	2,555	2,318	2,726	2,473	45'-6"	13.87	59'-6"	18.14
	18	E-05418 †	101,874	2,691	2,441	2,870	2,604	48'-2"	14.69	62'-2"	18.96
	19	E-05419 †	107,017	2,827	2,565	3,015	2,736	50'-10"	15.48	64'-10"	19.75
	20	E-05420 †	112,159	2,963	2,688	3,160	2,867	53'-6"	16.31	67'-6"	20.57
	21	E-05421 †	117,302	3,099	2,811	3,305	2,998	56'-2"	17.13	70'-2"	21.40
	22	E-05422 †	122,444	3,234	2,934	3,450	3,130	58'-10"	17.92	72'-10"	22.19
	23	E-05423 †	127,586	3,370	3,057	3,595	3,261	61'-6"	18.75	75'-6"	23.01
	24	E-05424 †	132,729	3,506	3,181	3,740	3,393	64'-2"	19.57	78'-2"	23.84
	25	E-05425 †	137,871	3,642	3,304	3,885	3,524	66'-10"	20.36	80'-10"	24.63
	26	E-05426 †	143,014	3,778	3,427	4,030	3,656	69'-6"	21.18	83'-6"	25.45
	27	E-05427 †	148,156	3,914	3,550	4,174	3,787	72'-2"	22.01	86'-2"	26.27
	28	E-05428 †	153,299	4,049	3,674	4,319	3,919	74'-10"	22.80	88'-10"	27.07
	29	E-05429 †	158,441	4,185	3,797	4,464	4,050	77'-6"	23.62	91'-6"	27.89
	30	E-05430 †	163,583	4,321	3,920	4,609	4,181	80'-2"	24.44	94'-2"	28.71
	31	E-05431 †	168,726	4,457	4,043	4,754	4,313	82'-10"	25.24	96'-10"	29.50
	32	E-05432 †	173,868	4,593	4,167	4,899	4,444	85'-6"	26.06	99'-6"	30.33
	33	E-05433 †	179,011	4,729	4,290	5,044	4,576	88'-2"	26.88	102'-2"	31.15
	34	E-05434 †	184,153	4,864	4,413	5,189	4,707	90'-10"	27.68	104'-10"	31.94
	35	E-05435 †	189,295	5,000	4,536	5,334	4,839	93'-6"	28.50	107'-6"	32.77
	36	E-05436 †	194,438	5,136	4,659	5,479	4,970	96'-2"	29.32	110'-2"	33.59
	37	E-05437 †	199,580	5,272	4,783	5,623	5,102	98'-10"	30.11	112'-10"	34.38
	38	E-05438 †	204,723	5,408	4,906	5,768	5,233	101'-6"	30.94	115'-6"	35.20
	39	E-05439 †	209,865	5,544	5,029	5,913	5,364	104'-2"	31.76	118'-2"	36.03
	40	E-05440 †	215,008	5,679	5,152	6,058	5,496	106'-10"	32.55	120'-10"	36.82



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height		
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters
60 Ft. (18.3 m)	8	E-06008	63,549	1,679	1,523	1,791	1,624	21'-6"	6.55	36'-11"	11.25
	9	E-06009	69,898	1,846	1,675	1,969	1,787	24'-2"	7.38	39'-7"	12.07
	10	E-06010	76,248	2,014	1,827	2,148	1,949	26'-10"	8.17	42'-4"	12.89
	11	E-06011	82,597	2,182	1,979	2,327	2,111	29'-6"	8.99	44'-11"	13.69
	12	E-06012	88,946	2,350	2,131	2,506	2,274	32'-2"	9.81	47'-7"	14.51
	13	E-06013	95,296	2,517	2,284	2,685	2,436	34'-10"	10.61	50'-4"	15.33
	14	E-06014	101,645	2,685	2,436	2,864	2,598	37'-6"	11.43	52'-11"	16.12
	15	E-06015	107,994	2,853	2,588	3,043	2,760	40'-2"	12.25	55'-7"	16.95
	16	E-06016	114,343	3,020	2,740	3,222	2,923	42'-10"	13.05	58'-4"	17.77
	17	E-06017	120,693	3,188	2,892	3,401	3,085	45'-6"	13.87	60'-11"	18.56
	18	E-06018	127,042	3,356	3,044	3,580	3,247	48'-2"	14.69	63'-7"	19.39
	19	E-06019	133,391	3,524	3,197	3,758	3,410	50'-10"	15.48	66'-4"	20.21
	20	E-06020	139,740	3,691	3,349	3,937	3,572	53'-6"	16.31	68'-11"	21.00
	21	E-06021	146,090	3,859	3,501	4,116	3,734	56'-2"	17.13	71'-7"	21.82
	22	E-06022	152,439	4,027	3,653	4,295	3,897	58'-10"	17.92	74'-4"	22.65
	23	E-06023	158,788	4,194	3,805	4,474	4,059	61'-6"	18.75	76'-11"	23.44
	24	E-06024	165,137	4,362	3,957	4,653	4,221	64'-2"	19.57	79'-7"	24.26
	25	E-06025	171,487	4,530	4,109	4,832	4,383	66'-10"	20.36	82'-4"	25.09
	26	E-06026	177,836	4,698	4,262	5,011	4,546	69'-6"	21.18	84'-11"	25.88
	27	E-06027	184,185	4,865	4,414	5,190	4,708	72'-2"	22.01	87'-7"	26.70
	28	E-06028	190,534	5,033	4,566	5,369	4,870	74'-10"	22.80	90'-4"	27.52
	29	E-06029	196,884	5,201	4,718	5,547	5,033	77'-6"	23.62	92'-11"	28.32
	30	E-06030	203,233	5,368	4,870	5,726	5,195	80'-2"	24.44	95'-7"	29.14
	31	E-06031	209,582	5,536	5,022	5,905	5,357	82'-10"	25.24	98'-4"	29.96
	32	E-06032	215,931	5,704	5,175	6,084	5,520	85'-6"	26.06	100'-11"	30.75
	33	E-06033	222,281	5,872	5,327	6,263	5,682	88'-2"	26.88	103'-7"	31.58
	34	E-06034	228,630	6,039	5,479	6,442	5,844	90'-10"	27.68	106'-4"	32.40
	35	E-06035	234,979	6,207	5,631	6,621	6,006	93'-6"	28.50	108'-11"	33.19
	36	E-06036	241,328	6,375	5,783	6,800	6,169	96'-2"	29.32	111'-7"	34.02
	37	E-06037	247,678	6,542	5,935	6,979	6,331	98'-10"	30.11	114'-4"	34.84
	38	E-06038	254,027	6,710	6,087	7,158	6,493	101'-6"	30.94	116'-11"	35.63
	39	E-06039	260,376	6,878	6,240	7,336	6,656	104'-2"	31.76	119'-7"	36.45
	40	E-06040	266,725	7,046	6,392	7,515	6,818	106'-10"	32.55	122'-4"	37.28



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height		
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters
72 Ft. (22.0 m)	8	E-07208	95,151	2,513	2,280	2,681	2,432	21'-6"	6.55	40'-5"	12.31
	9	E-07209	104,295	2,755	2,499	2,939	2,666	24'-2"	7.38	43'-1"	13.14
	10	E-07210	113,439	2,997	2,718	3,196	2,900	26'-10"	8.17	45'-8"	13.93
	11	E-07211	122,584	3,238	2,938	3,454	3,133	29'-6"	8.99	48'-5"	14.75
	12	E-07212	131,728	3,480	3,157	3,712	3,367	32'-2"	9.81	51'-1"	15.58
	13	E-07213	140,872	3,721	3,376	3,969	3,601	34'-10"	10.61	53'-8"	16.37
	14	E-07214	150,016	3,963	3,595	4,227	3,835	37'-6"	11.43	56'-5"	17.19
	15	E-07215	159,160	4,204	3,814	4,485	4,068	40'-2"	12.25	59'-1"	18.01
	16	E-07216	168,305	4,446	4,033	4,742	4,302	42'-10"	13.05	61'-8"	18.81
	17	E-07217	177,449	4,687	4,252	5,000	4,536	45'-6"	13.87	64'-5"	19.63
	18	E-07218	186,593	4,929	4,471	5,258	4,770	48'-2"	14.69	67'-1"	20.45
	19	E-07219	195,737	5,170	4,691	5,515	5,003	50'-10"	15.48	69'-8"	21.24
	20	E-07220	204,882	5,412	4,910	5,773	5,237	53'-6"	16.31	72'-5"	22.07
	21	E-07221	214,026	5,654	5,129	6,030	5,471	56'-2"	17.13	75'-1"	22.89
	22	E-07222	223,170	5,895	5,348	6,288	5,705	58'-10"	17.92	77'-8"	23.68
	23	E-07223	232,314	6,137	5,567	6,546	5,938	61'-6"	18.75	80'-5"	24.51
	24	E-07224	241,458	6,378	5,786	6,803	6,172	64'-2"	19.57	83'-1"	25.33
	25	E-07225	250,603	6,620	6,005	7,061	6,406	66'-10"	20.36	85'-8"	26.12
	26	E-07226	259,747	6,861	6,225	7,319	6,639	69'-6"	21.18	88'-5"	26.94
	27	E-07227	268,891	7,103	6,444	7,576	6,873	72'-2"	22.01	91'-1"	27.77
	28	E-07228	278,035	7,344	6,663	7,834	7,107	74'-10"	22.80	93'-8"	28.56
	29	E-07229	287,179	7,586	6,882	8,092	7,341	77'-6"	23.62	96'-5"	29.38
	30	E-07230	296,324	7,827	7,101	8,349	7,574	80'-2"	24.44	99'-1"	30.21
	31	E-07231	305,468	8,069	7,320	8,607	7,808	82'-10"	25.24	101'-8"	31.00
	32	E-07232	314,612	8,311	7,539	8,865	8,042	85'-6"	26.06	104'-5"	31.82
	33	E-07233	323,756	8,552	7,758	9,122	8,276	88'-2"	26.88	107'-1"	32.64
	34	E-07234	332,900	8,794	7,978	9,380	8,509	90'-10"	27.68	109'-8"	33.44
	35	E-07235	342,045	9,035	8,197	9,638	8,743	93'-6"	28.50	112'-5"	34.26
	36	E-07236	351,189	9,277	8,416	9,895	8,977	96'-2"	29.32	115'-1"	35.08
	37	E-07237	360,333	9,518	8,635	10,153	9,211	98'-10"	30.11	117'-8"	35.87
	38	E-07238	369,477	9,760	8,854	10,411	9,444	101'-6"	30.94	120'-5"	36.70
	39	E-07239	378,622	10,001	9,073	10,668	9,678	104'-2"	31.76	123'-1"	37.52
	40	E-07240	387,766	10,243	9,292	10,926	9,912	106'-10"	32.55	125'-8"	38.31



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height		
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters
75 Ft. (22.9 m)	9	E-07509	114,155	3,015	2,736	3,216	2,918	24'-2"	7.38	43'-2"	13.17
	10	E-07510	124,077	3,278	2,973	3,496	3,172	26'-10"	8.17	45'-11"	13.99
	11	E-07511	133,999	3,540	3,211	3,776	3,425	29'-6"	8.99	48'-7"	14.81
	12	E-07512	143,922	3,802	3,449	4,055	3,679	32'-2"	9.81	51'-2"	15.61
	13	E-07513	153,844	4,064	3,687	4,335	3,932	34'-10"	10.61	53'-11"	16.43
	14	E-07514	163,767	4,326	3,924	4,614	4,186	37'-6"	11.43	56'-7"	17.25
	15	E-07515	173,689	4,588	4,162	4,894	4,440	40'-2"	12.25	59'-2"	18.04
	16	E-07516	183,611	4,850	4,400	5,174	4,693	42'-10"	13.05	61'-11"	18.87
	17	E-07517	193,534	5,112	4,638	5,453	4,947	45'-6"	13.87	64'-7"	19.69
	18	E-07518	203,456	5,374	4,876	5,733	5,201	48'-2"	14.69	67'-2"	20.48
	19	E-07519	213,379	5,636	5,113	6,012	5,454	50'-10"	15.48	69'-11"	21.31
	20	E-07520	223,301	5,899	5,351	6,292	5,708	53'-6"	16.31	72'-7"	22.13
	21	E-07521	233,223	6,161	5,589	6,571	5,962	56'-2"	17.13	75'-2"	22.92
	22	E-07522	243,146	6,423	5,827	6,851	6,215	58'-10"	17.92	77'-11"	23.74
	23	E-07523	253,068	6,685	6,064	7,131	6,469	61'-6"	18.75	80'-7"	24.57
	24	E-07524	262,990	6,947	6,302	7,410	6,722	64'-2"	19.57	83'-2"	25.36
	25	E-07525	272,913	7,209	6,540	7,690	6,976	66'-10"	20.36	85'-11"	26.18
	26	E-07526	282,835	7,471	6,778	7,969	7,230	69'-6"	21.18	88'-7"	27.01
	27	E-07527	292,758	7,733	7,016	8,249	7,483	72'-2"	22.01	91'-2"	27.80
	28	E-07528	302,680	7,995	7,253	8,528	7,737	74'-10"	22.80	93'-11"	28.62
	29	E-07529	312,602	8,257	7,491	8,808	7,991	77'-6"	23.62	96'-7"	29.44
	30	E-07530	322,525	8,520	7,729	9,088	8,244	80'-2"	24.44	99'-2"	30.24
	31	E-07531	332,447	8,782	7,967	9,367	8,498	82'-10"	25.24	101'-11"	31.06
	32	E-07532	342,369	9,044	8,204	9,647	8,751	85'-6"	26.06	104'-7"	31.88
	33	E-07533	352,292	9,306	8,442	9,926	9,005	88'-2"	26.88	107'-2"	32.67
	34	E-07534	362,214	9,568	8,680	10,206	9,259	90'-10"	27.68	109'-11"	33.50
	35	E-07535	372,137	9,830	8,918	10,485	9,512	93'-6"	28.50	112'-7"	34.32
	36	E-07536	382,059	10,092	9,156	10,765	9,766	96'-2"	29.32	115'-2"	35.11
	37	E-07537	391,981	10,354	9,393	11,045	10,020	98'-10"	30.11	117'-11"	35.94
	38	E-07538	401,904	10,616	9,631	11,324	10,273	101'-6"	30.94	120'-7"	36.76
	39	E-07539	411,826	10,879	9,869	11,604	10,527	104'-2"	31.76	123'-2"	37.55
	40	E-07540	421,749	11,141	10,107	11,883	10,780	106'-10"	32.55	125'-11"	38.37



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height		
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters
105 Ft. (32.0 m)	12	E-10512	301,431	7,962	7,223	8,493	7,705	32'-2"	9.81	59'-11"	18.26
	13	E-10513	320,883	8,476	7,690	9,041	8,202	34'-10"	10.61	62'-6"	19.05
	14	E-10514	340,334	8,990	8,156	9,589	8,699	37'-6"	11.43	65'-2"	19.87
	15	E-10515	359,786	9,504	8,622	10,137	9,197	40'-2"	12.25	67'-11"	20.70
	16	E-10516	379,237	10,018	9,088	10,686	9,694	42'-10"	13.05	70'-6"	21.49
	17	E-10517	398,689	10,532	9,554	11,234	10,191	45'-6"	13.87	73'-2"	22.31
	18	E-10518	418,141	11,045	10,020	11,782	10,688	48'-2"	14.69	75'-11"	23.13
	19	E-10519	437,592	11,559	10,486	12,330	11,185	50'-10"	15.48	78'-6"	23.93
	20	E-10520	457,044	12,073	10,953	12,878	11,683	53'-6"	16.31	81'-2"	24.75
	21	E-10521	476,495	12,587	11,419	13,426	12,180	56'-2"	17.13	83'-11"	25.57
	22	E-10522	495,947	13,101	11,885	13,974	12,677	58'-10"	17.92	86'-6"	26.37
	23	E-10523	515,399	13,614	12,351	14,522	13,174	61'-6"	18.75	89'-2"	27.19
	24	E-10524	534,850	14,128	12,817	15,070	13,672	64'-2"	19.57	91'-11"	28.01
	25	E-10525	554,302	14,642	13,283	15,618	14,169	66'-10"	20.36	94'-6"	28.80
	26	E-10526	573,753	15,156	13,749	16,166	14,666	69'-6"	21.18	97'-2"	29.63
	27	E-10527	593,205	15,670	14,215	16,714	15,163	72'-2"	22.01	99'-11"	30.45
	28	E-10528	612,657	16,184	14,682	17,262	15,660	74'-10"	22.80	102'-6"	31.24
	29	E-10529	632,108	16,697	15,148	17,811	16,158	77'-6"	23.62	105'-2"	32.06
	30	E-10530	651,560	17,211	15,614	18,359	16,655	80'-2"	24.44	107'-11"	32.89
	31	E-10531	671,011	17,725	16,080	18,907	17,152	82'-10"	25.24	110'-6"	33.68
32	E-10532	690,463	18,239	16,546	19,455	17,649	85'-6"	26.06	113'-2"	34.50	
33	E-10533	709,915	18,753	17,012	20,003	18,146	88'-2"	26.88	115'-11"	35.33	
34	E-10534	729,366	19,266	17,478	20,551	18,644	90'-10"	27.68	118'-6"	36.12	
35	E-10535	748,818	19,780	17,945	21,099	19,141	93'-6"	28.50	121'-2"	36.94	
36	E-10536	768,269	20,294	18,411	21,647	19,638	96'-2"	29.32	123'-11"	37.76	
37	E-10537	787,721	20,808	18,877	22,195	20,135	98'-10"	30.11	126'-6"	38.56	
38	E-10538	807,173	21,322	19,343	22,743	20,632	101'-6"	30.94	129'-2"	39.38	
39	E-10539	826,624	21,836	19,809	23,291	21,130	104'-2"	31.76	131'-11"	40.20	
40	E-10540	846,076	22,349	20,275	23,839	21,627	106'-10"	32.55	134'-6"	41.00	



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK® EVEREST® NARROW-CORRUGATION STIFFENED GRAIN STORAGE FLAT-BOTTOM BINS

Bin Size			Maximum Capacity* - Peaked Storage				Eave Height		Fill Height		
Diameter	Rings	Bin Model	Bushels	U.S. Tons Corn	Metric Tons Corn	U.S. Tons Wheat	Metric Tons Wheat	Feet/Inches	Meters	Feet/Inches	Meters
132 Ft. (40.2 m)	18	E-13218	688,033	18,175	16,488	19,386	17,587	48'-2"	14.69	83'-11"	25.57
	19	E-13219	718,766	18,986	17,224	20,252	18,373	50'-10"	15.48	86'-7"	26.40
	20	E-13220	749,498	19,798	17,961	21,118	19,158	53'-6"	16.31	89'-4"	27.22
	21	E-13221	780,230	20,610	18,697	21,984	19,944	56'-2"	17.13	91'-11"	28.01
	22	E-13222	810,962	21,422	19,434	22,850	20,729	58'-10"	17.92	94'-7"	28.83
	23	E-13223	841,694	22,234	20,170	23,716	21,515	61'-6"	18.75	97'-4"	29.66
	24	E-13224	872,426	23,045	20,907	24,582	22,300	64'-2"	19.57	99'-11"	30.45
	25	E-13225	903,158	23,857	21,643	25,448	23,086	66'-10"	20.36	102'-7"	31.27
	26	E-13226	933,890	24,669	22,380	26,314	23,872	69'-6"	21.18	105'-4"	32.10
	27	E-13227	964,622	25,481	23,116	27,180	24,657	72'-2"	22.01	107'-11"	32.89
	28	E-13228	995,355	26,293	23,853	28,045	25,443	74'-10"	22.80	110'-7"	33.71
	29	E-13229	1,026,087	27,104	24,589	28,911	26,228	77'-6"	23.62	113'-4"	34.53
	30	E-13230	1,056,819	27,916	25,325	29,777	27,014	80'-2"	24.44	115'-11"	35.33
	31	E-13231	1,087,551	28,728	26,062	30,643	27,799	82'-10"	25.24	118'-7"	36.15
	32	E-13232	1,118,283	29,540	26,798	31,509	28,585	85'-6"	26.06	121'-4"	36.97
	33	E-13233	1,149,015	30,352	27,535	32,375	29,370	88'-2"	26.88	123'-11"	37.76
	34	E-13234	1,179,747	31,163	28,271	33,241	30,156	90'-10"	27.68	126'-7"	38.59
	35	E-13235	1,210,479	31,975	29,008	34,107	30,942	93'-6"	28.50	129'-4"	39.41
36	E-13236	1,241,211	32,787	29,744	34,973	31,727	96'-2"	29.32	131'-11"	40.21	
156 Ft. (47.5 m)	18	E-15618	995,146	26,287	23,848	28,040	25,437	48'-2"	14.69	90'-10"	27.68
	19	E-15619	1,038,074	27,421	24,876	29,249	26,535	50'-10"	15.48	93'-6"	28.50
	20	E-15620	1,081,003	28,555	25,905	30,459	27,632	53'-6"	16.31	96'-2"	29.32
	21	E-15621	1,123,931	29,689	26,934	31,668	28,729	56'-2"	17.13	98'-10"	30.11
	22	E-15622	1,166,860	30,823	27,962	32,878	29,827	58'-10"	17.92	101'-6"	30.94
	23	E-15623	1,209,788	31,957	28,991	34,087	30,924	61'-6"	18.75	104'-2"	31.76
	24	E-15624	1,252,717	33,091	30,020	35,297	32,021	64'-2"	19.57	106'-10"	32.55
	25	E-15625	1,295,646	34,225	31,049	36,507	33,119	66'-10"	20.36	109'-6"	33.38
	26	M-15626	1,338,574	35,359	32,077	37,716	34,216	69'-6"	21.18	112'-2"	34.20

* **Maximum Capacity** for a bin allows for grain to be at a 28° angle of repose, starting one inch (25 mm) below the eave. The grain capacities listed above are based on ASAE Standard S413.1, with a compaction factor of 6%. Metric tons are based on the ASAE Standard D241.4 of 721 kg per cubic meter for corn and 772 kg per cubic meter for wheat. Bins are designed to meet ASCE 7-10 code requirements for 105 mph (169 km/h) wind zones and UBC 97 seismic zone 1. Standard roof peak capacities vary from 2,500 to 130,000 pounds (1,100 to 59,000 kg) depending on bin diameter and ground snow load. In the pursuit of LEADERSHIP THROUGH INNOVATION®, we reserve the right to change specifications without prior notice.

¹ Some stiffened bins 48 and 54 feet (14.6 and 16.5 m) in diameter require a temperature cable package to be added during construction if temperature cables are desired.

² Fill height for 48-foot (14.6-m) diameter bins with standard farm roof. Brock's structured commercial roof is optional on these 48-foot diameter models. Brock's structured commercial roof is standard on the remaining 48-foot models and on all bins 54 feet (16.5 meters) in diameter and larger.

Because you will customize your grain storage system to your unique needs, not all potentially dangerous or harmful situations can be identified by Brock Grain Systems at the time the silo components and accessories are manufactured. Therefore, it is essential that you think safety first and pay close attention to all possible hazards.